



unigy I[®]

12AVR100ET

- Front access terminals
- Absorbed glass mat construction
- Tank formed plates optimize cell voltage balance
- Reinforced case resists bulging and meets safety requirements (UL 94 V0 / > 28% L.O.I.)
- Computer-aided design and manufacturing ensure quality products through control of process and standards
- All batteries meet or exceed IEEE 485 and Bellcore capacity requirements at shipment.
- Battery design and construction meet the requirements for UL recognition.
- I.C.A.O., I.M.D.G., I.A.T.A. and D.O.T. air transport approved.



QUALITY SYSTEM
CERTIFIED TO
ISO 9001
ISO/TS 16949
ISO 14001

SPECIFICATIONS

Nominal Voltage: 12-Volt

Positive Plate: Pure lead, low-calcium, high-tin alloy

Negative Plate: Lead calcium alloy

Post Seal: Epoxy-sealed

Terminal: Front access, 1/4" x 20 studs

Container: Flame-retardant, polypropylene - UL 94 V0 / >28% L.O.I.

Safety Vent: Low positive pressure, self-sealing with flame arrestor

Float Voltage: 2.27 volts per cell \pm 0.01 vpc (13.62 volts per 6-cell unit)

Design Life: 10 years in float applications at 77°F/25°C

Dimensions: 20.13" L x 4.33" W x 9.38" H

Weight: 75 lbs.

A.H. CAPACITY PER BATTERY

Volts Per Cell (V.P.C.)	2 HR	3 HR	4 HR	5 HR	6 HR	8 HR	10 HR	12 HR	20 HR	24 HR
1.75	76.0	81.0	84.9	88.1	91.0	96.0	100	102.1	108	110

DISCHARGE RATE IN AMPS

Volts Per Cell (V.P.C.)	2 HR	3 HR	4 HR	5 HR	6 HR	8 HR	10 HR	12 HR	20 HR	24 HR
1.75	38.0	27.0	21.2	17.6	15.2	12.0	10	8.5	5.4	4.6

"POWERED FOR PERFORMANCE"®

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781

Order Department Hotline: 610-682-4231

www.eastpenn-deka.com • e-mail: sales@eastpennunigy.com